


AD

TECHNICAL REPORT ARCCB-TR-95007

**FRACTURE TOUGHNESS ASSESSMENT OF PRESENT
AND FUTURE PRESSURE VESSEL MATERIALS BASED
ON CHARPY IMPACT ENERGY AND YIELD STRENGTH**

**EDWARD TROIANO
GREGORY VIGILANTE**



FEBRUARY 1995



**US ARMY ARMAMENT RESEARCH,
DEVELOPMENT AND ENGINEERING CENTER
CLOSE COMBAT ARMAMENTS CENTER
BENÉT LABORATORIES
WATERVLIET, N.Y. 12189-4050**



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

19950510 043

DTIC QUALITY INSPECTED 8

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DESTRUCTION NOTICE

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19 or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1995		3. REPORT TYPE AND DATES COVERED Final
4. TITLE AND SUBTITLE FRACTURE TOUGHNESS ASSESSMENT OF PRESENT AND FUTURE PRESSURE VESSEL MATERIALS BASED ON CHARPY IMPACT ENERGY AND YIELD STRENGTH			5. FUNDING NUMBERS AMCMS No. 6111.02.H611.1 PRON No. 1A11Z1CANMBJ	
6. AUTHOR(S) Edward Troiano and Gregory Vigilante				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-95007	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Several medium and high strength alloys, including AF1410, Inconel 718, PH 13-8 Mo stainless steel, and ASTM A723 high strength low alloy steel, have been heat treated to various strength and toughness levels and evaluated for correlations between fracture toughness and Charpy impact energy. The correlations investigated included those by Rolfe-Novak and Ault-Wald-Bertolo. Previous work by Kapp and Underwood suggests that for A723 steel, the Rolfe-Novak correlation predicts the fracture toughness reasonably well. One potential limitation of their study was that the Charpy impact energy was measured at -40°F, whereas the toughness was evaluated at room temperature. This study evaluates Charpy impact energy and toughness at both room temperature and at -40°F and considers both when utilizing these correlations. Results of this study indicate that the Rolfe-Novak correlation overpredicts the measured fracture toughness at room temperature, and tends to underpredict the measured fracture toughness at -40°F. The Ault-Wald-Bertolo correlation, in all but one instance, was a conservative estimate of the measured fracture toughness of the material at both room temperature and -40°F. Utilizing the results presented in this study, it is recommended that if a correlation is necessary for estimating the toughness of any of these materials, the Ault-Wald-Bertolo correlation will result in a conservative estimate of toughness.				
14. SUBJECT TERMS Fracture Toughness, Charpy Impact Energy, Yield Strength, Rolfe-Novak Correlation, Ault-Wald-Bertolo Correlation, AF1410, Inconel 718, PH13-8 Mo, A723 Steel			15. NUMBER OF PAGES 8	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
RESULTS	1
CONCLUSIONS	2
REFERENCES	3

TABLES

1.	Compilation of Strength and Toughness Data Used for Analysis	4
----	--	---

LIST OF ILLUSTRATIONS

1.	K _J (72°F) Versus CVN (72°F)	5
2.	K _J (-40°F) Versus CVN (-40°F)	6
3.	K _J (72°F) Versus CVN (-40°F)	7

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTRODUCTION

Because of the complexities of fracture testing, and the inability of many labs to conduct a fracture toughness test, many labs will simply measure the Charpy impact energy (CVN) and use one of many CVN- K_{Ic} correlations (ref 1) to predict the toughness of the material being investigated. This study examines two well-known correlations that are applicable in the upper-shelf regime. The two correlations studied are the Rolfe-Novak correlation (ref 2)

$$\left(\frac{K_{Ic}}{\sigma_{ys}}\right)^2 = 5\left(\frac{CVN}{\sigma_{ys}} - 0.05\right) \quad (1)$$

and the Ault-Wald-Bertolo correlation (ref 3)

$$\left(\frac{K_{Ic}}{\sigma_{ys}}\right)^2 = 1.37\left(\frac{CVN}{\sigma_{ys}}\right) - 0.045 \quad (2)$$

where σ_{ys} is the 0.2 percent yield strength.

These correlations were developed by compiling a large amount of data and curve-fitting the best linear fit to derive these equations. The Rolfe-Novak study included data from steels with yield strengths in excess of 100 Ksi, while the Ault-Wald-Bertolo study included only ultra-high strength steels (tensile strengths in the range of 200 Ksi to 300 Ksi). Although some of the materials utilized in this study do not fit these classifications, the correlation is still being investigated.

Since the materials being considered all possessed relatively high fracture toughness, even at -40°F, full J-integral (J_{Ic}) fracture toughness tests were conducted according to ASTM E-813, "Standard Test Method for J_{Ic} , A Measure of Fracture Toughness."

Elastic fracture mechanics (K_{Ic}) does not adequately predict the toughness of these materials because we cannot meet the K_{Ic} test requirements, per ASTM E-399, "Standard Test Method for Plane-Strain Fracture Toughness of Metallic Materials." Therefore, we have utilized elastic-plastic fracture mechanics (J_{Ic}) and converted the results to K_J with the following equation:

$$K_J = \sqrt{\frac{EJ_{Ic}}{1-\nu^2}} \quad (3)$$

These K_J values are believed to be good estimates of K_{Ic} .

RESULTS

The results of testing can be observed in Table 1. Note that both CVN and K_J were evaluated at both room temperature (72°F) and -40°F. The data presented in this table are the result of averaging a minimum of three test results for each condition.

The results presented in Table 1 are also shown graphically in Figures 1 and 2. The Rolfe-Novak correlation conservatively predicts the measured fracture toughness of all materials investigated, except for the AF1410. In the case of AF1410, it appears that the Ault-Wald-Bertolo correlation predicts the measured fracture response very accurately.

Figure 3 is significant since it attempts to predict the room temperature fracture toughness response based on -40°F CVN. Again, the Rolfe-Novak correlation does seem to conservatively predict the fracture toughness response (with a few outlier, especially at higher toughness values). As seen in Figure 3, the PH 13-8 Mo stainless steel is not conservatively predicted at room temperature based on a -40°F CVN.

CONCLUSIONS

1. Previous work by Kapp and Underwood (ref 4) indicated that for A723 steel, the Rolfe-Novak correlation predicts the fracture toughness response at room temperature reasonably well based on a -40°F CVN. This study verifies those findings. We have also found that Rolfe-Novak conservatively predicts the room temperature fracture toughness of Inconel 718 and the higher strength levels of AF1410 when based on -40°F CVN. However, the PH 13-8 Mo and the lower strength levels of AF1410 do obey this trend.
2. We have determined that the Rolfe-Novak correlation does not adequately or conservatively predict the fracture toughness at room temperature when estimated by room temperature CVN. Under these conditions, the Ault-Wald-Bertolo correlation does indeed conservatively predict the fracture toughness for all materials investigated.
3. Rolfe-Novak does conservatively predict the -40°F fracture toughness of A723, Inconel 718, and PH 13-8 Mo when based on -40°F CVN. Whereas it does not adequately predict the -40°F fracture toughness of AF1410 when based on -40°F CVN. For this material, the Ault-Wald-Bertolo correlation does predict accurate fracture toughness.
4. Based on the findings of this study, it appears that the accuracy of the two correlations studied is dependent on material tested, heat treatment condition, and test temperature. One general conclusion that can be drawn from this analysis is that the Ault-Wald-Bertolo correlation in most every case studied, conservatively estimated the fracture toughness of each of these materials, heat treatments, and test temperatures. However, the prediction is extremely conservative in many cases. This suggests that whenever an accurate representation of these classes of materials is necessary, a J_{Ic} fracture toughness test must be performed.

REFERENCES

1. *Metals Handbook*, Ninth Edition, Vol. 8, American Society for Metals, Metals Park, OH, 1985, pp. 264-267.
2. S.T. Rolfe and S.R. Novak, "Slow-Bend K_{Ic} Testing of Medium-Strength High-Toughness Steels," *Review of Developments in Plane-Strain Fracture Toughness Testing*, ASTM STP 463, American Society for Testing and Materials, Philadelphia, PA, 1970, pp. 124-159.
3. *Rapid Inexpensive Tests For Determining Fracture Toughness*, National Academy of Science, Washington, DC, 1976.
4. J.A. Kapp and J.H. Underwood, "Correlation Between Fracture Toughness, Charpy V-Notch Impact Energy, And Yield Strength for ASTM A723 Steel," *PVP-Vol 238, Codes and Standards and Applications for High Pressure Vessel Equipment*, ASME, 1992, pp. 219-221.

Table 1 - Compilation of strength and toughness data used for analysis

Material	Condition	.2% Y.S. (ksi)	CVN (72F) (ft-lbs)	CVN (-40F) (ft-lbs)	K _J (72F) (lbs/in)	K _J (-40F) (lbs/in)	CVN(72F)/YS (ft-lbs/ksi)	CVN(-40F)/YS (ft-lbs/ksi)	(K _J 72F)/YS ² (in)	(K _J -40F)/YS ² (in)
AF1410	HT #1	189	69	52	148	104	0.365	0.275	0.613	0.303
	HT #2	219	49	31	186	91	0.224	0.142	0.721	0.173
	HT #3	212	50	33	174		0.236	0.156	0.674	
	HT #4	213	48	40	174	107	0.225	0.188	0.667	0.252
Inconel 718		167	18	18	123	123	0.108	0.108	0.542	0.542
PH 13-8 Mo	HT #5	177	90	68	206	239	0.508	0.384	1.355	1.823
	HT #6	185	60	60	210	237	0.324	0.324	1.289	1.641
A723		168	28	22	118	113	0.167	0.131	0.493	0.452
		115	15	8	61	40	0.130	0.070	0.281	0.121
		155	31	13	100	95	0.200	0.084	0.416	0.376
		149	31	21	109	106	0.208	0.141	0.535	0.506
		117	14	6	57	51	0.119	0.051	0.237	0.190
		160	28	11	102	100	0.175	0.069	0.406	0.391
		148	33	22	107	114	0.216	0.149	0.523	0.593
		185	19	19	102	106	0.103	0.103	0.304	0.328
		153	47	37	131	148	0.307	0.242	0.733	0.936

HT #1	HT #2	HT #3	HT #4	HT #5	HT #6
1650F-1hr,AC	1650F-1hr,AC	1650F-1hr,AC	1650F-1hr,AC	1700F-1hr,AC	1700F-1hr,AC
1525F-1hr,AC	1525F-1hr,AC	1525F-1hr,AC	1525F-1hr,AC	1700F-1hr,AC	1700F-1hr,AC
-100F-1hr,AW	-100F-1hr,AW	-100F-1hr,AW	-100F-1hr,AW	1025F-5hr,AC	1025F-3hr,AC
400F-5hr,AC	925F-5hr,AC	950F-5hr,AC	975F-5hr,AC		




Figure 1 - K_J (72F) vs CVN (72F)

Solid lines represent correlations, dotted lines represent best linear fit of data being studied




Figure 2 - K_J (-40F) vs CVN (-40F)

Solid lines represent correlations, dotted lines represent best linear fit of data being studied




Figure 3 - K_j (72F) vs CVN (-40F)
 Solid lines represent correlations, dotted lines
 represent best linear fit of data being studied

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
CHIEF, DEVELOPMENT ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-DA	1
-DB	1
-DC	1
-DD	1
-DE	1
CHIEF, ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-E	1
-EA	1
-EB	1
-EC	
CHIEF, TECHNOLOGY DIVISION	
ATTN: AMSTA-AR-CCB-T	2
-TA	1
-TB	1
-TC	1
TECHNICAL LIBRARY	
ATTN: AMSTA-AR-CCB-O	5
TECHNICAL PUBLICATIONS & EDITING SECTION	
ATTN: AMSTA-AR-CCB-O	3
OPERATIONS DIRECTORATE	
ATTN: SMCWV-ODP-P	1
DIRECTOR, PROCUREMENT & CONTRACTING DIRECTORATE	
ATTN: SMCWV-PP	1
DIRECTOR, PRODUCT ASSURANCE & TEST DIRECTORATE	
ATTN: SMCWV-QA	1

NOTE: PLEASE NOTIFY DIRECTOR, BENÉT LABORATORIES, ATTN: AMSTA-AR-CCB-O OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH AND DEVELOPMENT ATTN: DEPT FOR SCI AND TECH THE PENTAGON WASHINGTON, D.C. 20310-0103	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-ENM ROCK ISLAND, IL 61299-5000	1
ADMINISTRATOR DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-OC (ACQUISITION GROUP) BLDG. 5, CAMERON STATION ALEXANDRIA, VA 22304-6145	2	MIAC/CINDAS PURDUE UNIVERSITY P.O. BOX 2634 WEST LAFAYETTE, IN 47906	1
COMMANDER U.S. ARMY ARDEC ATTN: SMCAR-AEE	1	COMMANDER U.S. ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIBRARY) WARREN, MI 48397-5000	1
SMCAR-AES, BLDG. 321	1	COMMANDER U.S. MILITARY ACADEMY	
SMCAR-AET-O, BLDG. 351N	1	ATTN: DEPARTMENT OF MECHANICS	1
SMCAR-FSA	1	WEST POINT, NY 10966-1792	
SMCAR-FSM-E	1		
SMCAR-FSS-D, BLDG. 94	1	U.S. ARMY MISSILE COMMAND	
SMCAR-IMI-I, (STINFO) BLDG. 59	2	REDSTONE SCIENTIFIC INFO CENTER	2
PICATINNY ARSENAL, NJ 07806-5000		ATTN: DOCUMENTS SECTION, BLDG. 4484	
		REDSTONE ARSENAL, AL 35898-5241	
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. ARMY FOREIGN SCI & TECH CENTER ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WT-PD (DR. B. BURNS) ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. ARMY LABCOM MATERIALS TECHNOLOGY LABORATORY ATTN: SLCMT-IML (TECH LIBRARY) WATERTOWN, MA 02172-0001	2
DIRECTOR U.S. MATERIEL SYSTEMS ANALYSIS ACTV ATTN: AMXSY-MP ABERDEEN PROVING GROUND, MD 21005-5071	1	COMMANDER U.S. ARMY LABCOM, ISA ATTN: SLCIS-IM-TL 2800 POWER MILL ROAD ADELPHI, MD 20783-1145	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER		WRIGHT LABORATORY	
U.S. ARMY RESEARCH OFFICE		ARMAMENT DIRECTORATE	
ATTN: CHIEF, IPO	1	ATTN: WL/MNM	1
P.O. BOX 12211		EGLIN AFB, FL 32542-6810	
RESEARCH TRIANGLE PARK, NC 27709-2211			
DIRECTOR		WRIGHT LABORATORY	
U.S. NAVAL RESEARCH LABORATORY		ARMAMENT DIRECTORATE	
ATTN: MATERIALS SCI & TECH DIV	1	ATTN: WL/MNMF	1
CODE 26-27 (DOC LIBRARY)	1	EGLIN AFB, FL 32542-6810	
WASHINGTON, D.C. 20375			

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.
